

SMARTCASE™ S501

Chassis Kit Solution



Mini-STX Motherboard
K3921-H, K3921-N

FOR

Industrial chassis for enhanced operating temperature range

- Ultra-Compact Design
- 36 x 147 x 165 mm
- Front & Rear USB
- VESA- and Wall Mount Option
- New Security Feature: Chassis Intrusion Option

kontron

CHASSIS DATA	DIMENSIONS COLOUR WEIGHT	36 x 147 x 165 mm (W x H x D) black ~ 0.4 kg
ENVIRONMENTAL CONDITIONS	OPERATING TEMPERATURE*	Passive Cooling: -10 °C ... +35 °C (tbd) ** Active Cooling: -10 °C ... +40 °C (tbd, up to 15 W TDP, any position)
	HUMIDITY	5 % - 85 % relative humidity (non-condensing)
APPROVALS & CERTIFICATIONS	EMC	Planned: CE Class B, Industrial Immunity (EN 61000-6-2), FCC-B/ICES-003 verified
PACKAGE CONTENT		Chassis desk stand (vertical mode, removable) Rubber feet (horizontal mode, removable) Chassis bottom/top incl. front bezel; Rear I/O with integrated EMI gasket
CHASSIS FEATURES	THEFT PROTECTION	Kensington lock support Mechanical lock for DC-In connector (DC-in holder; optional)
	MOUNTING OPTIONS	Intrusion Support (optional) Integrated WLAN antennas Wall Mount VESA Kit Cooling solution Rear COM port
REQUIREMENTS FOR AC ADAPTER	SAFETY	Compliance with IEC 62368-1 according clause 6.2.2. to power source category PS2 ("Limited Power Source") required!

* Chassis ambient temperature; upper limit depends on system configuration
 ** Limited cooling performance in horizontal operating mode; possible system performance reduction.
 Vertical operating position recommended for most favorable cooling & system performance



F5000-C024

- Specific passive heatsink designed for SMARTCASE™ S501
- Max. 9 W TDP
- Weight ~ 180g





F5000-C026

- Specific active heatsink designed for SMARTCASE™ S501
- Max. 15 W TDP
- Weight ~ 200 g



Chassis Front/Rear View (Horizontal Position)

Motherboard K3921-N installed



Overview Chassis Configuration/Options

	K3921-H	K3921-Nx
SMARTCASE™ S501 Rev. 01	yes	yes
Chassis Rear Wall (up to 2x Graphics + COM) included in chassis kit	yes	yes
Passive Cooling (F5000-C024) supported	yes	yes
Active Cooling (F5000-C026) supported	yes	yes
Rear COM Port Option S26361-F5000-K007 supported	yes	yes
2nd LAN Port supported	no	yes

ARTICLE	PART NO.	DESCRIPTION
SMARTCASE™ S501	F5000-J014	10x chassis kit

Accessories

VESA MOUNTING KIT	S26361-F5000-X002	VESA adapter incl. mounting screws
AC ADAPTER 19V / 65W	S26361-F5000-P006	AC Adapter, 19 V/3.4 A, 65 W
INTERNAL WLAN ANTENNA KIT	S26361-F5000-W005	WLAN antenna kit; left (grey)/right (black) antennas incl. cable. M.2 WLAN module not included!
INTERNAL WLAN ANTENNA KIT	F5000-W006	Box contains 10 dual antennas (incl. antenna cable) for SMARTCASE™ S5xx series. Additional support for WiFi 6E/WiFi 7; replaces F5000-W005
WALLMOUNT BRACKETS	S26361-F5000-X001	2x Brackets per chassis incl. screws
DC-IN HOLDER	S26361-F5000-X003	Holder incl. screws
HEATSINK	F5000-C024	Specific passive heatsink (max. 9 W TDP) for SMARTCASE™ S501
HEATSINK	F5000-C026	Specific active heatsink (max. 15 W TDP) for SMARTCASE™ S501
INTERNAL REAR COM PORT CABLE	S26361-F5000-K007	w/o slot bracket, length = 120 mm, 2 mm pitch internal connector
CHASSIS INTRUSION KIT FOR SC-S501	F5000-K017	Contains 20x chassis intrusion cable plus 20x mounting bracket for K3921/SMARTCASE™ S501

Global Headquarters

Kontron Europe GmbH

Gutenbergstraße 2
85737 Ismaning, Germany
Tel.: + 49 821 4086-0
info@kontron.com

www.kontron.com

